

## BLACK RT series Online UPS


6K/10K



## **KEY FEATURE**

- True double-conversion design with high adaptability to harsh mains conditions
- Ideal to for high-end equipment which are sensitive to power quality
- · Supports energy-saving ECO mode
- Wide input range (120-276V<sub>AC</sub>)
- Intelligent communication slot enables remote monitoring
- · Precise output voltage regulation
- Rack/tower dual set-up with rotatable LCD panel
- Intelligent Charging Management\* for batteries prolongs battery life

## **Typical Application**























## **Specification**

Model		BLACK RT 6K	BLACK RT 6KS	BLACK RT 10K	BLACK RT 10KS	
Capacity		6000VA/5400W 10000VA/9000W				
Input	Input Voltage Range	120~276V <sub>AC</sub>				
	Frequency Range	45-55Hz / 54-66Hz				
	Input Wiring	Single phase with ground				
	Current Distortion (THDi)	<5% @ full load				
Output	Output Power Factor	0.9				
	Nominal Output Voltage	208/220/230/240V <sub>AC</sub>				
	Voltage Regulation	±1%				
	Frequency Range ( Battery Mode )	50/60 ± 0.1 Hz				
	Current Crest Ratio	3:1				
	Voltage Distortion (THDv)	<2% @ Linear Load, <5% @Non-Linear Load				
	Output Waveform	Pure Sine Wave				
	Parallel Operation	Up to 2 units				
Efficiency	Inverter Mode	92%		93%		
	Battery Mode	89%		90%		
	ECO Mode	96%		97%		
Battery	Battery Type	12V/5Ah	N/A	12V/9Ah	N/A	
	Number of Internal Battery	15	N/A	20	N/A	
	Rated Battery Voltage	180V <sub>DC</sub>		240V <sub>DC</sub>		
	Backup Time (@ Full Load)	>2.5mins	N/A	> 3.5mins	N/A	
	Recharge Time (to 90%)	3 hours	N/A	3 hours	N/A	
	Charging Current	1A	8A	1.7A	8A	
Transfer Time	Battery Mode ↔ Inverter Mode	0 ms				
	Inverter Mode ↔ Bypass Mode	0 ms				
	ECO Mode ↔ Battery Mode	<10 ms				
Display		LCD				
Audible Alarm		Yes				
Dimension	WxHxD	438 x 129 x 698 mm	438 x 129 x 640 mm	438 x 215.5 x 704 mm	438 x 215.5 x 640 mm	
Net Weight		46kg	19 kg	82.5kg	26kg	
Environment	Operating Temperature	0-40° C	0-40° C			
	Noise Level	<55dB @ 1 Meter				
Interface	RS232/USB	Yes				
	External Slot	Yes				
	Emergency Power Off	Yes				

**KOLFF**. Chile

Santiago +56 2 2570 6300 www.kolff.cl KOLFF. Perú

Lima +51 1 208 9170 www.kolff.com.pe **KOLFF**. Argentina

Buenos Aires +54 11 4313 1836 www.kolff.com.ar KOLFF. Brasil

São Paulo +55 11 5524 1029 www.kolff.com.br